



Total Solution Provider in Saw Device

SA710BM

Wireless, RF SAW Filter
Revision 0: July 2012



- Electrical Characteristics
 - Package Dimensions
 - Testing Environment
 - Frequency Characteristics
-

SAWNICS Inc.

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / www.sawnics.com



□ Electrical Characteristics

Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	0	-	+50
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	0
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	M			
Length x Width	mm ²	-	3.0 x 3.0	-
Height	mm	-	-	1.3

Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	710.0	-
Insertion Loss within 704.0 ~ 716.0 MHz	dB	-	1.9	2.5
Amplitude Ripple within 704.0 ~ 716.0 MHz	dB _{p-p}	-	0.8	1.2
Attenuation:				
725.0 MHz	dB	12	17	-
734.0 ~ 746.0 MHz	dB	35	47	-
Return Loss within 704.0 ~ 716.0 MHz	dB	10	12	-

Notes : No Matching Network (Ref. Testing Environment Circuit as shown below).


Package Dimensions



Marking Descriptions	
d	Wireless Application
H	Series Number
X	Date Code(Year)
Y	Date Code(Month)

Pin Description	
A, C, D, F	Ground
E	In or Out
B	Out or In



Testing Environment



Source & Load Impedance: 50 Ω



□ Frequency Characteristics

Frequency Response





Return Loss



Smith Chart

