



Total Solution Provider in Saw Device

SA957AM

Wireless, RF SAW Filter
Revision 1: July 2009



- Electrical Characteristics
 - Package Dimensions
 - Testing Environment
 - Frequency Characteristics
-

SAWNICS Inc.

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / www.sawnics.com

□ Electrical Characteristics

Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-30	-	+65
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	0
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	M			
Length x Width	mm ²	-	3.0 x 3.0	-
Height	mm	-	-	1.3

Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	957.25	-
Insertion Loss				
953.0 ~ 964.0 MHz	dB	-	2.8	3.3
942.25 ~ 972.25 MHz	dB	-	4.5	5.5
Amplitude Ripple within 953.0 ~ 964.0 MHz	dB _{p-p}	-	0.5	1.0
Attenuation:				
D.C ~ Fo-45.0 MHz	dB	45	55	-
Fo+70.0 ~ Fo+500.0 MHz	dB	50	60	-
VSWR within 953.0 ~ 964.0 MHz	-	-	1.5	2.0

Notes : (1) No Matching Network (Ref. Testing Environment Circuit as shown below).


Package Dimensions



Marking Descriptions	
L	Wireless Application
e	Series Number
X	Date Code(Year)
Y	Date Code(Month)

Pin Description	
A, C, D, F	Ground
E	In
B	Out



Testing Environment





Source & Load Impedance: 50 Ω

□ Frequency Characteristics

Frequency Response



VSWR



Smith Chart

